



for cleaner nature we work . . .



PAMATKOMPLEKTĀCIJA		Merv. / kods	Viscomat Gear 200/2 M	Viscomat Gear 230/3 M	Viscomat Gear 350/2 M	Viscomat Vane 70 M	Viscomat Vane 90 M	Viscomat 60/1 24V/12V	Viscomat 60/2 24V/12V	Viscomat 120/1 24V/12V
Tehniskie parametri	Elektropieslēgums (spriegums)	V	230	230	230	230	230	24V   12V	24V   12V	24V   12V
	Plūsmas ātrums	l/min	<9	<14	<9	<25	<50	<4	<10	<5
	Spiediens	bar	12	12	25	6	5	5	4	10
	Sūkņa jauda	W	550	750	750	750	1600	-	-	-
	Sūkņa apgriezieni minūtē	apgr/m	1450	1450	1450	1450	1450	-	-	-
	Sūkņa ieplūdes/izplūdes savienojuma izmērs	collas	1"	1"	1"	1"	1"	1/2"	3/4"	1/2"
	Sūkņa trokšņu līmenis	dB	<70	<70	<70	<70	<70	<65	<65	<65
	Sūkņa darbības cikls	min	∞	∞	∞	∞	∞	30min	30min	30min
	Viskozitāte	cSt	<2000	<2000	<2000	<500	<500	<2000	<600	<2000
	Apvadventīlis (By Pass)		x	x	x	x	x	-	-	-
	Atloka savienojums		-	x	x	x	-	-	-	-
	Ieslēgšanas / izslēgšanas slēdzis		x	x	x	x	x	x	x	x
	Šķidrums, kurus drīkst pārsūknēt (Eļļa, Rapšu eļļa)		E	E	E	E,R	E,R	E	E	E
	Aizsardzības klase IP		IP55	IP55	IP55	IP55	IP55	IP55	IP55	IP55
	Iepakojuma izmēri	mm	350x200x280	350x200x280	350x200x280	350x200x280	350x200x280	255x125x150	355x195x270	355x195x270
Svars	kg	9	12.5	12.5	14.1	14.1	3	4.9	4.9	
<b>Cena ar PVN 21%:</b>			<b>221.49</b>	<b>275.04</b>	<b>275.04</b>	<b>211.6</b>	<b>283.07</b>	<b>175.19</b>	<b>194.25</b>	<b>194.25</b>
Spiediena relejs Flowmat	F003020_		171.56	170.65	170.65	-	-	-	-	101.19